



SYMBOLS	MIN.	NOR.	MAX.
A	-	-	0.210
A1	0.015	-	-
A2	0.125	0.130	0.135
D	1.230	1.250	1.280
E	0.300 BSC.		
E1	0.253	0.258	0.263
L	0.115	0.130	0.150
eB	0.335	0.355	0.375
θ°	0	7	15

UNIT : INCH

NOTES:

1. JEDEC OUTLINE : MS-001 AF
2. "D", "E1" DIMENSIONS DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED .010 INCH.
3. eB IS MEASURED AT THE LEAD TIPS WITH THE LEADS UNCONSTRAINED.
4. POINTED OR ROUNDED LEAD TIPS ARE PREFERRED TO EASE INSERTION.
5. DISTANCE BETWEEN LEADS INCLUDING DAM BAR PROTRUSIONS TO BE .005 INCH MINIMUM.
6. DATUM PLANE [E] COINCIDENT WITH THE BOTTOM OF LEAD, WHERE LEAD EXITS BODY.

P/N: AP89085 - SKDIP - G



比例 SCALE	材質 MATERIAL	數量 QTY
圖名 TITLE	圖號 PART NO.	日期 DATE
製圖 DRAWN	審核 CHECKED	日期 DATE
日期 DATE	日期 DATE	日期 DATE
APP: Erik	FILE: J1-0124K-001-02	DATE: 02
		頁數 PAGE: 1